

Model: AK-C115W



System	WEB	Default account and password : admin
	P2P	Free, Plug and Play, no port forwarding
	APP	Android: search EasyN P in Google play or visit p.easyn.cn / p.easyn.com for APP download iOS: search EasyN P in Appstore for APP download.
	PC Client CMS	1,4,9,16,25,36 multi windows in center management system, recording and alarm
	System and browser	Microsoft Win98 SE/ME/2000/XP、Vista、Win 7, Internet Explorer 6.0/7.0/8.0/9.0/10, FireFox, Google , Safari
Main chipset	operation system	Linux
	DSP	32Bit RSIC Embedded Processor
	Sensor	1/2.7" CMOS
	Memory	64M(DSP built-in)
	FLASH	16M
Video	Compression format	H.264
	Pixel	2 Megapixel
	Frame rate	50Hz: 1~20fps , 60Hz: 1~25fps
	Resulotion	(1920*1080),VGA(640*352),QVGA(320*176)
	Image adjustment	The hue, brightness, contrast, saturation and sharpness are adjustable
	LUX	0.4 Lux/F2.0
	SNR	>48DB
	Shutter	1/50s(1/60s) ~ 1/100,000 s
	Lens	M12/2.1mm F2.0 , angle of view 150 ° (Diagonal) 3X digital zoom
	WB&BLC	Auto

Night vision	IR	SMT 5050 3pcs LED lights, Wavelength 850nm , IR angle 150 °
	Distance	IR distance 10m, photoresistor sensitivity: 0~5 Lx
	IR-CUT	Auto switch , without color cast
Audio	Talk	Two way audio
	Format	G711/726
	Speaker	1W, 8Ω
	Microphone	-52dB
Structure	IR-CUT	Auto switch , without color cast
	Cruise	IE support auto cruise and 8 preset positions.
Network	Wire	RJ-45 10/100Mb
	Online limit	Up to 3 visitors online for the first stream, Up to 3 visitors online for the second stream, Total up to 6 visitors online.
	Support IP address	Static IP, Dynamic IP, PPPOE
	Protocal	Support TCP/IP、HTTP、ICMP、DHCP、FTP、SMTP、PPPoE and so on
Wireless	WIFI	WIFI IEEE 802.11B/G/N
	Antenna	2.4GHz built-in antenna
	Transmission rate	150Mbps (Max)
	Mode	QR code
Recording	Type	TF card , support 24 hours continuous recording.
	Micro SD size	2G/4G/8G/16G/32G/64G 128G max.
	Format	AVI
	Protocal	Compatible with onvif 2.1
Housing	Material	Plastic (ABS + PC)
Power	Power	DC5V 1A USB
	Frequency	50Hz / 60Hz
Environment	Assembly	Indoor
	Temperature	-10~50 °C

	Humidity	10% ~ 90% RH
Packing	Box	Color box and carton, 60pcs/CTN
	Dimension	Product size: Φ 80*35mm (L*W*H) box size: 11*9.5*8cm (L*W*H) CTN SIZE:50*40*40cm approx. (L*W*H)
	Weight	N.W: 85g , G.W: 0.21kg (including box) CNT Weight: 14kg (only for reference)
	Accessories	Power adapter, manual, screws , Warranty card
Alarm	Input/output	none
	Motion detection	Support 1 detection area for mobile and 4 areas for PC
	Alarm notification	Push notification for iPhone/Android APP Upload pictures to only one email address, three pictures to the max. Upload snapshot and alarm records to TF card (when insert Micro TF card) and FTP server
Certificate	Certificate	ISO FCC CE